

### **GOVT. GIRLS POLYTECHNIC**

# Byron Bazar, Raipur-492 001, C.G. शासकीय कन्या पॉलीटेक्निक

बैरन बाजार, रायपुर- 492 001, छ.ग.

Web Site: http://ggpraipur.ac.in e-Mail: principal.ggpraipur@gmail.com Phone.: 0771-2423045

## **TENDER NOTICE – 02/EQUIP/ 2021-22**

# "OPEN TENDER FORM FOR SUPPLY OF LABORATORY MACHINES AND EQUIPMENT"

Total no of pages: 45





GOVT. GIRLS POLYTECHNIC

Byron Bazar, Raipur-492 001, C.G. शासकीय कन्या पॉलीटेक्निक

बैरन बाजार, रायपुर- 492 001, छ.ग.

Web Site: http://ggpraipur.ac.in\_e-Mail: principal.ggpraipur@gmail.com\_Phone.: 9771-2423945

TENDER NOTICE – 02/EQUIP/2021-22

NOTICE INVITING OPEN TENDER FOR THE SUPPLY OF
LABORATORY MACHINES AND EQUIPMENT

NO- GGPR/Store /TENDER/MACHINES & EQUIP./2021-22/ 194, RAIPUR Dated: 30-10-202

Government Girls Polytechnic, Raipur invites open tenders of amount Rs.54.10 lakhs approx. (in words: Rupees fifty-four lakh ten thousand approx.) from OEMs/ Manufacturer/ Authorized Distributor/ Dealer/ Supplier/ Seller/ Reseller of LABORATORY MACHINES AND EQUIPMENT FOR VARIOUS DEPARTMENTS (ET&T, Architecture & IDD, MOM, CDDM, Pharmacy, Language Lab.) of the institute. Tender document can be obtained from the Institute's account office during the office working hours only, except public holiday, on payment by cash or by Demand Draft of Rs.1,500/- (Rupees One Thousand five hundred Only) in favour of, The Principal, Government Girls Polytechnic, Byron-Bazar, Raipur, payable at Raipur.

Tender document can also be downloaded from website <a href="www.ggpraipur.ac.in">www.ggpraipur.ac.in</a> or <a href="cgdteraipur.cgstate.gov.in">cgdteraipur.cgstate.gov.in</a> if, downloaded from the website the tenderer /bidder has to submit the Demand-Draft (DD) tender fee amounting Rs. 1,500/- (Rupees One Thousand five hundred Only), in favour of, The Principal, Government Girls Polytechnic, Byron-Bazar, Raipur, payable at Raipur, with the submission of the Tender-Bid. Else, otherwise, the bid is liable to be cancelled. The above said tender fee is non-refundable.

Important Dates and Timings:

Tender form price	Rs 1,500/- (Rupees One Thousand five hundred Only				
Date for sale of tender document	Date: 02.11.2021from 11:00 AM				
Last date for Sale of Tender Document	Date: 02.12.2021 up to 12:00 PM				
Last date for Submission of Sealed Tender	Date: 02.12.2021 up to 02:00 PM				
Date of opening the Tenders received	Date: 02.12.2021 at 03:00 PM				
Venue of opening the Tenders	Principal's Office, Government Girls Polytechnic, Byron bazaar, Raipur				

Note:- Tender for laboratory machines and equipment are grouped according to the various departments of the institute. Tenderer / bidder may apply for one or many groups of departments as per choice.



Principal Govt. Girls Polytechnic, Raipur

#### **TENDER DOCUMENT**

1. TENDER NO.

: NO- GGPR/Store /TENDER/MACHINES &

EQUIP./ 2021-22/ 1194 Raipur, Date 30-10-2021

2. COST OF THE TENDER FORM

: Rs. 1,500/- by Cash or DD, Non-refundable

3. SALE OF TENDER DOCUMENT

: Starts on 02.11.2021 from 11:00 AM to 02.12.2021 up to 12.00 PM

4. DATE OF SUBMISSION

: On or before 02.12.2021 /02:00 PM

5. DATE OF TENDER / BID OPENING: On 02.12.2021 / 03:00 PM
Note: In case, if the last date is declared to be a Gazetted / Closed Govt. holiday, the date of submission and opening shall be immediate next working day.

6. The tender shall be opened at 3.00 PM of the last day of submission i.e 02.12.2021 at Principal's Office, Government Girls Polytechnic, Raipur. The Tenderer/Bidder Authorized Representatives of the Tenderer/Bidder may be present.

7. Tender shall remain valid for a period of one year.

- 8. Scope of supply- Supply of items as stated in ANNEXURE- III
- 9. Essential Qualifications of the Tenderer/ Bidder
  - i. The Tenderer/ bidder must have valid PAN/ TAN, GSTIN.
  - ii. Latest GST Clearance Certificate.
  - iii. Tenderer / Bidder must be OEMs/ Manufacturer/ Authorized Distributor/ Dealer/ Supplier/ Seller/ Reseller (Tick Appropriate) submit the relevant Certificate / Authority letter(s).

Or else Tenderer/ Bidder of the tender will be treated as cancelled.

- 10. Tenderer/ Bidder must submit- the Main Envelope -4 which must contain Envelope-1-EMD, Envelope-2- Technical bid, and Envelope-3 Price/ Commercial bid.
- 11. Preparation of Envelopes: -

#### **ENVELOPE -1**

EMD - A Demand Draft of minimum Rs. 5000 or 3% of the total bidding amount (Refer point 12) quoted by the Tenderer/ bidder in price bid whichever is more must be submitted, in favour of The Principal, Government Girls Polytechnic, Byron-Bazar, Raipur-492001, payable at Raipur.

### **ENVELOPE -2**

All the relevant documents duly self-attested with seal by the Tenderer/ bidder regarding the essential qualification of the Tenderer/ bidder should be kept as per ANNEXURE-I (Essential qualification of the Tenderer/ Bidder) and ANNEXURE-II



S. no.	Essential documents to be submitted as per Annexure I  Tenderer / Bidder is OEMs/ Manufacturer/ Authorized Distributor/ Dealer/ Supplier/ Seller/ Reseller (Tick Appropriate) submit the relevant Certificate /
1.	l'enderer / Bluder is (Tiel Appropriate) Subilité de
	Supplier/ Seller/ Reseller (Tick Approx
	Supplier/ Seller/ Reseller (Tick Appropriate Authority letter(s).  Year of starting of the firm with registration Number & Date. (Attach relevant
2.	Year of starting of the firm with registration
	document)
3.	PAN (Attach copy)
4.	GSTIN Registration (Attach copy)
5.	GST clearance certificate latest. (Attach copy)
6.	
7.	Income tax return for the last three financial years (Attach copy)  Annual turnover for last three years (balance sheet) (Attach copy)

#### **ENVELOPE -3**

It should contain the quoted price on the prescribed format ANNEXURE-III (Price Bid). Inside Envelope-3, the price bid of various chosen groups must be kept in separate envelopes super scribed with group name.

The quoted price should be inclusive of all the taxes, duties and any other levies/charges with all the discounts and/or any offers.

#### **ENVELOPE -4**

All the envelopes marked as ENVELOPE -1, ENVELOPE -2, ENVELOPE -3 must be kept in ENVELOPE- 4

- a. Offer will be accepted in sealed envelopes with (Envelope -4) cover super scribed as "Tender for laboratory machines and equipment in Govt. Girls Polytechnic Raipur (C.G.)" The Main envelope should contain three inner envelopes containing Envelope-1- EMD, Envelope- 2 - Technical bid and Envelope- 3- price bid in the prescribed forms super scribed as "Tender for laboratory machines and equipment in Govt. Girls Polytechnic Raipur (C.G.) Earnest Money Deposit (EMD)", "Tender for laboratory machines and equipment in Govt. Girls Polytechnic Raipur (C.G.) Technical Bid" and "Tender for laboratory machines and equipment in Govt. Girls Polytechnic Raipur (C.G.) - Price Bid" respectively.
- b. Sequence of opening the Envelopes:
  - Envelope-1 EMD
  - ii. Envelope-2 (Technical-Bid) will be considered for opening after receiving the valid
  - iii. After the satisfactory evaluation of Technical-Bid, Envelope -3 (Price-Bid) will be considered for opening.
  - iv. The date for opening of Price/ Commercial Bid (Envelope -3) will be declared on the date of the opening of the tender.
- c. All the Envelopes should be signed, sealed and taped on all joints. GRIS

4

d. Tender submitted by fax or e-mail shall not be accepted.

e. All the pages of the tender-document including ANNEXURE-I, ANNEXURE-II & ANNEXURE-III, shall be duly signed by the Tenderer/ bidder.

f. Quoted Price should be written legibly in words & Figures. If any difference is observed the rates given in words shall be taken as final.

g. The Tenderer/ bidder is expected to carefully examine all instructions, forms, terms and specifications in the tender document.

h. The bid must be in line with specifications and conditions required in the tender. It should be valid for one year from the date of opening of bids.

i. Overwriting should be avoided. Overwriting, erasures and other changes should bear the dated initials of the person signing the tender.

j. Failure to furnish complete information, required as per the tender document or submission of bid not substantial, will be rejected.

k. This tender form is non-transferable.

1. Deduction of taxes/ levies at the source would be made by this office as and when required as per Government rules.

m. Item no. and page no. of the tender form should be strictly in chronological order.

n. Make, name of the manufacturer with complete address must be mentioned against each item and equipment.

o. Relevant brochures and real image / photographs of the equipment/ laboratory machinery for authentication of the desired material must be enclosed.

p. The tender should clearly indicate whether the equipment is complete in itself, if in the opinion of the tenderer/ bidder certain accessories are necessary with the type of the equipment tendered, the tenderer/ bidder must quote for aforesaid accessories separately under the heading Extra but Essential.

#### 12. **Earnest Money Deposit (EMD)**

Requisite EMD in the form of Demand Draft of minimum Rs. 5000 or 3% of the total bidding amount quoted by the Tenderer/ bidder in price bid whichever is more must be submitted, in favour of The Principal, Government Girls Polytechnic, Byron-Bazar, Raipur-492001, payable at Raipur. The tenderer / bidder can choose and quote prices for any one or many groups from the list hale

, , , , , , , , , , , , , , , , , , , ,	or many groups from the list below:-		
Group	Machines and equipment of laboratories.	Abbreviation	Amount in lakhs (approx.)
Group A	Electronics and Telecommunication Lab.	Et&T	25.00
Group B	Architecture & Interior Decoration and Design Lab.	Arch.& IDD	21.25
Group C	Modern Office Management lab.	MOM	0.05
Group D	Costume Design and Dress Making Lab.	CDDM	0.85
Group E	Pharmacy Lab.		2.00
Group F	Digital Language Lab software	Pharmacy	1.00
	Digital Danguage Lab software	Language Lab.	4.00
	1,520	Total	54.10
	In words: Rupees Fifty-four	r lakh ten thousar	d Approx.

EMD of the unsuccessful tenderer / bidder will be refunded without interest to the tenderer / bidder in due course of time. The EMD will be treated as security deposit in case of selected tenders.

The EMD shall be forfeited if, the tenderer / bidder amends, impairs or derogates from the tender in any respect within the validity period of their tender / bid.

Payment Terms

- a. 100% payment will be released after the successful Delivery, installation and demonstration of the laboratory machines / equipment at institute as per the delivery schedule in the purchase order.
- b. No advance payments shall be made.
- c. There is no provision for partial payments against any supply of the items.
- d. No payment shall be made for the damaged or rejected items.

14. Delivery

- a. After receiving of the purchase order (PO), the delivery of items must be made as per schedule mentioned in the purchase order.
- b. Supply shall be given, at Government Girls Polytechnic, Raipur on FOR basis.

#### 15. Other Terms & Conditions

- a. A prospective Tenderer/ Bidder requiring any clarification regarding the tender document may notify this office in writing at the address indicated at the cover of the tender document. The office would respond in writing to any request for clarification of the tender document provided that it is received not later than seven days prior to the last date prescribed for submission of tenders. However, the office shall not be responsible for any delays.
- b. The Supplier is not allowed to transfer, assign or sublet the order in full or any part thereof directly or indirectly.
- c. The tenderer / bidder should quote their rates strictly adhering to terms and conditions stipulated in the tender document. Unsolicited correspondence after opening of the tender shall not be entertained. Conditional / deviational tenders may be rejected without making any reference to the Tenderers / Bidders.
- d. No Tenderers / Bidders will be allowed to withdraw his tender during the validity period, or else, the undersigned reserves the right to forfeit the EMD / Security deposit.
- e. In case of any default in execution of the order the undersigned reserves the right to forfeit the EMD / Security deposit.
- f. The undersigned also reserves the right to cancel the order and forfeit the EMD/ Security deposit in case the tenderer /bidder fails to adhere strictly to all terms and condition of the order / tender.


GIRL

g. If supplier expresses his inability to execute the order for the items or rate or makes / brand mentioned in the tender within validity period, the undersigned also reserves the right to forfeit the EMD/ Security deposit.

h. The warranty period for the equipment supplied by the supplier will have to be mentioned clearly which should not be less than one year from the date of installation. The tenderer /bidder will be responsible for repair / replacement of defective parts T/C of as per warranty.

i. Canvasing in any form for acceptance of the tender bid is liable to be disqualified.

- j. Selected Tenderer/ bidder must demonstrate the working and functioning of the item/ appliances before the authorized committee appointed by this office. The purchase order will be placed only after satisfactory review/ report of the item / appliances by the said committee.
- k. The training for handling the laboratory machines / equipment shall be provided by the supplier at his own cost. The tenderer/ bidder must give demonstration of the equipment / software at the Institute.
- 1. This office will not pay any amount for transit and insurance of the material.
- m. Exact and earliest possible time of delivery should be indicated in the tender against each item. The delivery period given in the order will be the date of receipt of the equipment in the institute and not the date of dispatch of the equipment by the supplier.
- n. The one-time extension in the delivery period may be granted at the discretion of the undersigned.
- o. If the successful tenderer/ bidder, on receipt of the order, fails to execute the order within the stipulated period, in full or part, it will be open to the Govt. Girls Polytechnic, Raipur to recover liquidated damage from the firm at the rate of 2% of the value of undelivered goods per month or part thereof, subjected to a maximum of 5% of the value of undelivered goods.
- p. No claim shall be entertained in respect of interest on Earnest Money / Security deposit.
- q. The Principal reserves the right to accept the lowest or any tender and also of rejecting in full or part thereof without assigning any reasons for the same or to split up the tender as he may deemed to be fit.
- r. The Principal reserves the right to cancel the tender in full or part thereof, if needed.
- s. In the event of any dispute arising out of the bid, the decision of The Principal, Govt. Girls Polytechnic, Raipur shall be final.
- t. In case of any dispute, it is subjected to the jurisdiction of district of Raipur, Chhattisgarh.



# LETTER OF SUBMISSION OF TENDER FROM BY THE TENDERER/ BIDDER (To be printed on tenderer/ bidder's letterhead)

# "Supply of Laboratory machines and Equipment at Government Girls Polytechnic, Raipur"

1.	Name and Address of th	e Firm	:	
2.			•	
		spondence		
3.	Telephone No ( Land-Li Mobile No. of Authorise			
	Valid Email id			
4.	Payment Details of Tend DD No / Cash Receipt N			
	Name of DD issuing ban	k :		Date
	Amount :	(in v	words)	
	Payable at	:Raipur (C.		
5.	Earnest Money Deposit (	EMD ) deta	ils.	
	DD No			_
				Date :
	Amount :	(in v	vords)	
	Payable at	:Raipur (C.	G.)	
6.	Whether Tenderer / Bidde	r is (Tick A	ppropriate)	
	OEMs/ Manufacturer/ Au	thorized Dis	stributor/ Dealer/ Suppl	ier/ Seller/ Reseller
	Please, attach the Certifica	ate / Author	ity letter(s)	
7.	Year of starting of the firm	with regis	tration Number & Date	e. (attach relevant document)

8.

PAN/TAN (Attach copy)

- 9. GSTIN Registration (Attach copy)
- 10. GST clearance certificate latest. (Attach copy)
- 11. Income tax return for the last three financial years (Attach copy)
- 12. Annual turnover for last three years (balance sheet) (Attach copy)
- 13. All the documents attached

attached r	must be duly self-attested by the tenderer/ bidder.
	Signature of the Authorized Signatory
lace:	Full Name
	Company Seal



# (To be printed on Tenderer/ bidder's letterhead)

# DECLARATIONS BY THE TENDERER / BIDDER

	· ·
1.	I, Son /Daughter of Shri
	Proprietor/ Partner/ CEO /MD/ Director/
	Authorized Signatory of M/s am competent
	to sign this declaration and execute this tender.
2.	I have carefully read and understood all the terms and conditions mentioned in the tender document and hereby convey my acceptance of the same.
3.	The information/ documents furnished along with the above application are true and authentic to the best of my knowledge and belief.
4.	I/we am/ are well aware of the fact that furnishing of any false information/ fabricated document would lead to rejection of my tender at any stage besides liabilities towards prosecution under appropriate law.
5.	Each page of the tender document and papers submitted by my Company is authenticated, and I take full responsibility for the entire documents submitted.
6.	I/We agree to pay all government (central and state of CG) Taxes such as GST, service tax etc. and other taxes prevailing from time to time and the rates quoted by me/us are inclusive of the same.

- 7. The rates quoted by me / us are firm and shall not be changed due to variations on account of fluctuation in the market rates, taxes or any other levies, whatsoever.
- 8. If this tender is accepted, I / we hereby agree to execute the purchase order in full and abide, fulfil all the terms, conditions and provisions of the tender.



9.	If We, further specifically certify that our orgation or put to any Holiday by any Institutions Undertaking in the last three years.	nization has not been Black Listed/De Listed al Agency/Govt. Department/Public Sector
10.	Names of the persons authorized to be present	at the time of opening of the tender
	i	
	ii	
		Signature of the Authorized Signatory
Date	te:	Full Name
Place	ce:	Company Seal



M.

## Group – A

# **Department – Electronics & Tele-Communication Engg.**


_		PRICE-BI	D			
स. इ.	मशीन उपकरण का नाम	स्पेशिफिकेशन	मात्रा	दर (जीएसटी सहित)	राशि	रिमार्क
•	DESKTOP	PROCESSOR	06-Nos.	(")		
	COMPUTER	Intel® Core™ i5-1135G7	00 1100.		Α.	
	( All in One )	Processor,11th Generation				
		(8-MB Cache, up to 4.2 GHz).				
		MEMORY				
		8-GB / DDR4 / 2666-MHz / (8-GBx1) Upgradable upto Min.32-GB				
		STORAGE		-		
		1-TB / 7200 RPM / 3.5" SATA Hard				
		Drive or better option				
		DVD-ROM, DVD+/-RW Super-Multi				
		and Slot-Load, Blu-ray Writer				
		MONITOR		-		
		Appx. 23-inch FHD (1920 x 1080) Anti-Glare Narrow Border AIT Infinity				
		Active Touch Screen Display				
		GRAPHICS				
		Intel® Iris® Xe Graphics with shared				
		graphics memory or better				
		CONNECTIVITY				
		Wi-Fi 802.11				
		Bluetooth 5.1 or higher. PORTS				
		1 X VGA				
		Min. 1 X HDMI			1 "	
		Min. 2 X USB 3.0 or Higher				
		Min. 2 X USB 2.0, 1 X RJ 45				
		KEYBOARD / MOUSE				
		Wireless Keyboard- Mouse				
		CAMERA			·	
		Full HD IR Web Camera				
		OPERATING SYSTEM				
		Windows 10 Pro 64 bit, English (				
		Latest Version )				
		ANTIVIRUS				
		- Bundled Antivirus / Malware with 3				
		years Subscription				
		SYSTEM WARRANTY & SUPPORT				
		- 3 years onsite OEM warranty.				
2	COMPUTER	PROCESSOR	03-Nos.			4
	WORKSTATION	- Intel Xeon W-2195 Processor / 2.3				
		GHz / 18-Cores				
		Up to 4.3 GHz with Intel Turbo     Boost Technology				
		- Cache - 24.75 MB				
		CHIPSET				
		Intel C422 Chipset (Intel Xeon W		;		1 4
		Processors)	TLY D			

		LANGUA (DAM)			
		MEMORY (RAM) - 32-GB (8 GB x 3) DDR4-2666			
		MT/s ECC Registered Divivio			
		- Supported up to 512-GB DDR4			
		DIMMS			
		- Memory configurations using 32-			
1		GB DIMMs with the Memory			
		Cooling Solution,			
		STORAGE - 2.5" SATA SSD 1-TB drives and			
		300-GB 15K SAS SFF Hard Drive			
		(with Controller add-in card)			
		- DVD-ROM, DVD+/-RW Super-Multi			
		and Slot-Load, Blu-ray Writer			
		<ul> <li>Min 02 - Internal 3.5-inch bays</li> </ul>			
		DISPLAY			
		- 23.8" Anti-Glare LED Monitor			1.5
		Screen - Res 1920 X 1080			
		GRAPHICS			
		- NVIDIA Quadro P400, 2-GB V-			
		RAM (GDDR5) Graphics			
		- (Based on GP107 Graphics			
		Processor, The card must support			
		DirectX 12.0)			
		INTERFACE & SOCKETS			
		- PCI Express Gen3x16 - PCI Express Gen3x16			
		mechanical/x8 electrical		1 "	
		- PCI Express Gen3x8			
		mechanical/x4 electrical;			
		- 1 Legacy PCI Slot			
		- Min. 02-Min DIN Ports for Key-			
		Board & Mouse			
		- Min. 02- USB ( 2.0 ) & Min. 04-USB			
		(3.0 or Higher)  - HDMI - Display Port, VGA Port			
		- Min 02- NIC - 10/100/1000 Gbps			
		RJ-45 Socket			
1		- Audio Port (Mic./Spk./Aux.)			
		OPERAING SYSTEM			
		- Windows 10 Pro 64 bit, English			
		(Latest Version)			
		<ul> <li>Red Hat Enterprise Linux Desktop / Workstation*</li> </ul>			
		(Preinstalled OS and 3-Years			
		paper licens)	- 7 -		
		ANTI-VIRUS			
		Bundled with 3-Years Subsription			
		Warranty			
		SYSTEM (Hardware) WARRANTY			
		3-Years On-Site Warranty			
	ETWORK				
0	SWITCH SOLLY	- Fully Managed L2 Switch	02-Nos.		,
3	0 2011	- 24-10/100 slots , 2-10/100/1000			
1	1 PLS	slots, 2-GbE SFP slots - Switching capacity - 56 Gbps		19	
	16	Power - AC 120/230 V (50/60			
1	E/ ~~/	Power - AC 120/230 V (50/60 Hz)	,		
1 1	3	→ 02 x Gigabit SFP			X. X.
	2/0/	7 02 x Combo Gigabit SFP			
100		Gigabit or Fast Ethernet ports			

	1				
		capabilities with PoE+ and 10-GbE Uplinks			The state of the s
		- IEEE 802.3 Ethernet MIB Repeater			
		MIB Ethernet interface MIB			
		serial RS-232C or micro USB /			
		802.3 Ethernet MIB Repeater MIB			
		Ethernet interface MIB			
		- DHCP-Protection, Dynamic ARP-			
		Protection, and Dynamic IP-			
		Lockdown,			
		- Enhance security / Flexible traffic			
		controls including ACLs and QoS			
4	4K - ULTRA HD	Power - AC 120/230 V (50/60 Hz)			
	SMART LET	PICTURE-PANEL /SCREEN	02-Nos.		
	SMART LED TV	- Around 65" View-Panel Size	UZ-NOS.		
		- Resolution - Ultra HD 3840 x			
		2160			
		Appx. 16.7 m Cont. Ratio			
		<ul> <li>Appx. 5000:1 Brightness: 700 cd m</li> </ul>			
		Appx. Response Time: 5 ms     Display Type, 4K LUID			
		- Display Type - 4K UHD			
	= =	<ul> <li>Viewing Angle - Wide Viewing Angle Appx. 170° (Angle &amp; H/V)</li> </ul>			
		- IPS Panel			
		PICTURE QUALITY / PROCESSING			
		- Picture Processor - Quad Core			
		Processor 4K			
		- Refresh Rate - 50 Hz			
		- HDR - 4K Active HDR / HDR 10			
		Pro / HDR Dynamic Tone			
		Mapping / HLG			
		Color Enhancer / True Color			
		Accuracy / Active Noise			. 7
		Reduction - Advance			
		<ul> <li>Resolution Upscaler - 4K</li> </ul>			<u> </u>
		Upscaler			
		<ul> <li>Supported Image Type - PSD.</li> </ul>			1
		TIFF, GIF, PNG, RAW, JPEG etc.			
		AI-FEATURES			1.
		<ul> <li>Al Enabled TV / Al Functions /</li> </ul>			1.
		Intelligent Edit			
		<ul> <li>Google Assistant, Amazon Alexa</li> </ul>			
		- Enabled			2
		<ul> <li>Apple - Apple Airplay 2, Apple</li> </ul>			
		HomeKit			
		<ul> <li>Intelligent Voice Recognition</li> </ul>			
		<ul> <li>Home Dashboard</li> </ul>			
		SMART TV FEATURES			÷.
		<ul> <li>Operating System - Android</li> </ul>			
		based WebOS			
1		<ul> <li>Remote Control</li> </ul>			
		<ul> <li>Full Web Browser</li> </ul>			
		<ul> <li>Direct Keys (Apps) - Netflix,</li> </ul>			***
		Prime Video			
		<ul> <li>Cloud Photo &amp; Video</li> </ul>		1	3.7
		AUDIO			124 122 1 1
		<ul> <li>Speaker System - 2.0-Channel</li> </ul>			
		Speaker			
	The state of the s	<ul> <li>Audio Output (rms) - 20 W</li> </ul>			
	SOIL.	<ul> <li>Al Acoustic Tuning</li> </ul>	,		
	1 DECOLITE	Clear Voice / Surround Sound -			
	CILS POLYTE	: \			2.1
	TO A PROPERTY OF				
,		*			
	15/ //	- /			11-
	181 /19	1		_	14-
	10	/			
	100 police /				
	N. K. Line				
	Marine and work of the last		* * * * * * * * * * * * * * * * * * * *		

$\Box$		DTS Virtual-X						
		- Bluetooth Audio Playback -2 w	ay					
		Playback						
		<ul> <li>Supported Audio Format -</li> </ul>						
		mp3_audio, wma						1
		<ul> <li>Media Format - AVI, Blu-ray,</li> </ul>						
		DVD, MPEG, WAV, WMA						
		CONNECTIVITY						
		- Built-in Wi-Fi	-					
		- Bluetooth - V 5.0 or higher /						
		Simplink (HDMI CEC)  - Share & Control Capable / Mob	oile					
		Connectivity						-
		INPUTS & OUTPUTS						
	5.1	- 01-DVI, 01-PC/VGA						
		– Min. 02-HDMI Input Version 2.0	0					
		or better '						
		<ul><li>Min. 02-USB Ports</li></ul>						1
		<ul> <li>01- RF Input / 01-AV / 01-Medi</li> </ul>	ia		100			
		Player						
	4	<ul> <li>LAN Connectivity</li> </ul>						
		<ul> <li>Optical Digital Audio Out</li> </ul>						
		POWER	^					
		- Power Supply (Voltage, Hz) -	AC					
	1 2	110~240V / 50-60 Hz						
		- Power Consumption Standby				-	-	
		Mode - Appx. 0.5 W ESSENTIAL ACCESSORIES						
		- Remote Control Module						
	- +	- Power source with AA or AA	A		2		-	
		1.5V, 2 Alkaline-Batteries						
,		<ul> <li>Operating Manual</li> </ul>					-	
		<ul> <li>HDMI Cable,</li> </ul>						
		<ul> <li>Wall Mount &amp; Table Mount</li> </ul>						
		Fixtures						
	51	- Warranty - 3-Years						
		Comprehensive Warranty		02-Nos.				
5	VIDEO CAMERA	Video Capture Resolution	Min '	02-1103.				
	(Professional	. 480p						
	Grade)	Maximum Focal Length						
		Maximum 1 oodi 2011ga	110					
	1.2	-mm (Standard)						
		Maximum Focal Length	18-					
		mm (Standard)						
		LOTTO	18 -					
		110 mm f/4 G OSS Lens (Zoom						
	9-3							
		Type) - E PZ With Lens Hood						
		E. II as a star a must anone	At					
1.	The same of the sa	Full aperture must opens 1.9 and also remains same during						
No.	GRULYTECH		Tele					
18/5	3	/ Wide shooting						
1 8	12121	Optical Sensor Technology			44 (3.4)			
XF		*	Su					
MENT		per 35-Sized APS-CMOS Power	= 1					
The second	121							
1		Zoom for 4K-Movies	00		16.72.2			
1	NOT KRAITS	Flash Memory Type	SD					
gi.	The Book St.	Interface / Connectivity	us					
The state of the s	그렇게 가셨다. 이렇게 취임 사람이 없다면 보다 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그							

HDD / SSD with USB 3.0. High-Resolution and Proxy clips can be extracted to USB storage at high speed. (For On-site backup) -Recording Built-in support for a wide variety of production formats :- High quality XAVC Intra and XAVC Long GOP recordings Broadcast-standard MPEG HD422 and MPEG HD DVCAM at 25 Mbps in MXF file format -Integrated Electronic Variable ND Filter -DCI 4K (4096 x 2160) up to 59.94p -UHD up to 59.94 fps, Frame Rate HD up to 180 fps, XAVC-I/L, MPEG-2, XAVC up to 600 Mb/s -Supports Rec. 709 and BT-2020 with **Dual XQD Memory Card Slots** -1 x 4K XDCAM Super 35 Camcorder Kit with as per above specifications ( 18-110mm Zoom Lens) -0.5-inch high quality OLED viewfinder (Display Min. 320 X 240 **AUDIO** - Professional Audio Capabilities With independent volume dials enabling Precision Control of external audio inputs. **ESEENTIAL BUNDLED WITH** - 120-GB G Series XQD Memory Card -1 x High Quality Dust Cleaner Blower -1 x SD Card USB Reader -1 x Memory Card Wallet -1 x Deluxe Cleaning Kit -1 x Microfiber Cloth -Original Lithium-Ion Battery with **Battery Charger** (Min. 2-Hour Battery Back-up) -2 x Power Cord -1 x 3-Piece LCD Screen Protector Kit ADDITIONAL ACCESSORIES -Tripod Stand - Load Capacity - Appx. 5 KG - Max Height - Appx. 60 Inches Min Height - Appx. / 26 Inches Folded Length - Appx. 30 Inche - Leg Sections - 3 Legs -Shoulder mount -Body Cap, -Viewfinder with Lens Hood, Eyepiece Front Lens Cap & Rear Lens Cap Grip Remote Control



		Wireless Adaptor Bracket			
	00111157.7	Lens Case	03-Nos.		
6	SOUNDBAR With	<ul> <li>Wall Mountable / Remote</li> <li>Controlled 2.1 Channel Sound-</li> </ul>			
	POWERED SUB-			-	
	WOOFER	Bar - Powered Wireless Sub-Woofer			
	(Professional	Bluetooth Connectivity 5.0 or			
	Grade)	Latest			
	Oraco,	For Wireless Audio Streaming			
		<ul> <li>Master Digital Amplifier with Pro</li> </ul>			
		Front Surround Sound			
		Dolby Digital / Dolby Dual Mono /	-		
		LPCM 2-Channel Optical Input			
	1	<ul> <li>TV Sync.(Connectivity)</li> </ul>			
		Wireless (Bluetooth) / HDMI-			
		Cable (ARC) / USB			
		- Wireless Powered Sub-Woofer			
		Various Standard Sound Output			
		Modes			
	7.	<ul> <li>Total Output must be around Appx. 300-Watt</li> </ul>		4	
		ACCESSORIES			
		- Operating Remote-Control			
	1	with Batteries			
	54	Optical & HDMI Cable (AV)			
		<ul> <li>Setup Guide and Instructional</li> </ul>			
	. 3-	Manual			
	Y	<ul> <li>Min. 1-Year Warranty</li> </ul>			
7	MULTI CHANNEL	Analog Audio Mixing	03-Nos.		
	AUDIO MIXER	Min. 02-Stereo & 01-Mono (Mic.)			
	(Professional	Input Channel		-	
	Grade)	/ 02-EQ Band and Min 02-Bus  – 01-Master Fader (60 mm)			
		= 01-Master Fader (60 mm) = 01-1/4" Input Socket for			
		Headphone Jack		=	
		<ul> <li>02-Nos. Stereo Channel with</li> </ul>			
		'Dual' ¼" Input			
	3.1	<ul> <li>CD / Tape I/O Connectivity with</li> </ul>			
		Min. 02-Nos.RCA Connections			
		<ul> <li>02-Nos. ¼" Output from Mixers</li> </ul>			
	3	Connectivity to Output systems			
		<ul> <li>Setup Guide and Instructional</li> </ul>			
		Sheet / Manual			
	14/1951 500	<ul><li>– Min. 1-Year Warranty</li><li>– Ceiling / Wall-Mount Wireless</li></ul>	05-Nos.	-	
8		Camera	05-1105.		
	SECURITY CAMERA	Outdoor / Weathe-Proof / Full HD			
	CAMERA	1080p / Bullet Camera			
	Aug.	Night vision (Appx. 30 Mtr.) /			
		HumanDetection (H265)			
	16 18	- Ethernet (RJ-45) / Wi-Fi (Appx.			
	The state of the s	2.4 GHz.) Base IP-Based / Wi-Fi			
	QULYTER.	Hotspot			
	15	Video / Audio Recording on SD-			
1	2.	Card			
A	\$1 N/X	(Compatible with Alexa Google			
- J - U		Assistant )			
X	F / / / 10	May OFC OD OD O	1		
K	1 0//3	- Max. 256-GB SD Card storage			
		supported / NVR Cloud			
	POLYTECHNICATION OF THE PROPERTY OF THE PROPER				

. 1	MICROSOFT				
		Microsoft Soft - Web Camera	T 00 11	-	
	WEB-CAMERA	- Video Capturing 4 0 MB 4 700	02-Nos.		
- 1	AMERICA	Video Capturing – 4.0 MP / 720p /			
- 1		Image Capturing Speed – 30fps – Zoom			
		20011			
		Optical – 10X and Digital – 4X			
		Additionatic Exposure Control			
		- Video /			
		Audio – Integrated Crystal			-4
-		Microphone	-		
		Omni-directional / Built in Noise			
		Reduction			A
		- Image: 1289 X 800 pixel for Still /	_ =		
		1280 X 720 pixel for Motion			
- 1		Image Frame Bote : 30 fee			
1		Image Frame Rate: 30 fps			
-		True-Color / Auto Image			
- 1		Adjustment			
- 1		24-Bit Color Depth / Wide-Screen			
- 1		Aspect Ratio 16:9			
		Fixed Foous Arms 00 MM			
		Fixed Focus : Appx. 03. Mtr. – 1.5			
- 1		Mtr.			
		<ul> <li>Setup Guide and Instructional</li> </ul>			
		Sheet / Manual			
+	CTUDIC	Min. 1-Year Warranty			
	STUDIO	Professional Grade Studio Microphone	02 N	 <u> </u>	
	MICROPHONE	- Dynamic Cardioid Bolar Bettern	03-Nos.		
	WITH	by namic Cardioid Polar Pattern			
	ALL FIXTURES &	<ul> <li>Flat Frequency Response for</li> </ul>			
-	ATTACHMENT	Wide Frequency Response ~ 40 -			
	ATTACHMENT	20000 Hz			
		− Dynamic Range ~ 112			
		dB Range			
-					
		- Current Consumption ~		1.	
		Appx. 5-mA			ų.
		<ul><li>Battery Life ~</li></ul>		1	
		Around 100 Hours appx.			
		For Vocal / Instrumental, Motion			4
		Picture / TV/ Popording / Death			
		Picture / TV Recording / Radio			
		Announcement & Production etc.			
-		<ul> <li>Audio – Integrated Condenser</li> </ul>		9	
		Microphone			
-		Omni-directional / Built in Noise			1.
		Reduction			
		FIXTURES & ACCESSORIES		1	
		<ul> <li>Metal Shock Mount</li> </ul>			T 3
		<ul> <li>Large 19-mm Diaphragm</li> </ul>			32
		Heavy Gauge Mesh Grill			7
		_			
		Poll Tune A=41 and at 5		9	
		Ball-Type Anti-wind Foam Cap./			· ·
		Mic. Pop Filter		ľ.	
		- Connectivity (Cable) : 3.5 mm			
		XLR and / or USB			
1		Setup Guide and Instructional			
	i.	Sheet / Manual		Ė	
1		Min. 1-Year Warranty			
	Portable Light-	Tripod. With its stable camera	03-Nos.		
	Weight Aluminium	support opens up all sorts of			
	Tripod for DSLR,	possibilities in terms of low-light			9
	Camera				
	Callicia	shooting, long exposures, panning			34 34 311.1
		shots, panoramas and more.			
		- PROFESSIONAL: Capture vivid,			
		professional-style photographs			16 7
	A COM	Lightweight Tripod and camera			
1	GIRLS POLL				
4	0	accessory for both, novice and		 1	
1	E CONTE	1		È	
i		**			
-	1 / 5				
5		1			18-
AL AA	A TOTAL	2			
AN THE	1 15	/		14	10
AN PARTY		/			10
CALM	70.			7	
CALIN	70s Raises			14	
CALM	TO RAIDE TO STATE OF THE PARTY				

		interpolation, without cumbersome welding procedures, time saving, convenient and quick	OVER THENT	100	1	19-
	Connectivity and Data Box HDMI VGA RJ45 USB 3.5 mm Audio Power Hidden Multimedia Desktop Socket	foam cushion and waterproof film - Panel Size: 266*130*7mm - Box Size: 280*170*100mm - Socket or cables: 2-universal power, 2-network, 1-vga,1-hdmi,1-ubs,1-audio, with 30cm connected cables	10/0	YTECHNIC	*	
1	Conference Table	- Material : high quality zinc alloy finishing panel, strong carton with	12-Nos		- too a she if a reasoning statement	
		PAL/N input formats and HDMI 480I/576I/480P/576P/720P/1080i/10 80p at 50 or 60Hz Includes 100-240 50/60 Hz auto switching power supply for use anywhere in the world, Lifetime Support & 12-Month Manufacturer's Warranty				
	Sp 10 1000p	- Input connections: HDMI, RCA Composite & Output connections: HDMI, 3.5mm Audio, Digital Audio - Perfect Conversion - Converts Any PAL (50hz) Signal to NTSC HDMI (60hz) 1080p, Converts any NTSC (60hz) to PAL HDMI (50hz) - Supports Analog PAL, NTSC3.58, NTSC4.43, SECAM, PAL/M and				
3	PAL HDMI / RCA Composite to NTSC HDMI 50/60 Hz Multi-System Video Converter - Up to 1080p	- Convert PAL/NTSC RCA Composite (Red, White, Yellow) or HDMI 50/60 Hz to HDMI 50/60Hz Converter - Automatically convert signals from PAL or NTSC analog to up to 1080p HDMI 50Hz or 60 Hz	05-Nos			
•	Aluminium Tripod for DSLR, Camera	cameras, digital cameras, still cameras, GoPro devices, Smartphone adapters and scopes - Operating Height: Appx. 5.5 Feet - Load Capacity: Appx. 5kg	OF No.			
2	Portable Lightweight	- HIGHLY COMPATIBILITY: Compatible with most video	06-Nos.	,		
		Legs are "multi-section" that can adjust the spread of the legs to allow the tripod to be used at different heights or in awkward areas where one leg or more legs cannot be at the same angle as the others.  - With locking facility in legs				
		Compatible with most video cameras, digital cameras, still cameras, GoPro devices, Smartphone adapters and scopes.  THREE SECTIONS FOR HEIGHT ADJUSTMENT				
		professional photographers alike, - Handy tripod accommodates a wide range of digital, video and still cameras and comes loaded with user-friendly features HIGHLY COMPATIBILITY:				

		- Kinds of multi-seed to the force it	T		
1		Kinds of multi-media interfaces, it			
1		can be hidden into the table so that			
		the messy cable on the table can be put together centrally			
		- The cold rolled steel a seed all and			
		The cold rolled steel panel, silent			
		designing, press the button then it			
		will open. Close the cover when you	, -		
		do not use it, dustproof. Noble,		= 1	
		elegant and durable			
15	115	Office, meeting room, multi-media			
13	HDMI to HDMI	classroom		Millionia de la companie de la comp	
	Augio Ontical	One HDMI Input to one HDMI	06-Nos		
	SPDIF + RCA	Output(Pass Mode), SPDIF			
	L/R Extractor	(Optical) digital audio			
	Converted	output(2CH/5.1CH Mode), and			
	Converter Audio	analog RCA L / R audio output(2CH			
	Splitter Media	Mode)			
	Streaming Device	<ul> <li>SPDIF and L/R audio support</li> </ul>	X		
	0 - 01100	output separately to amplifier			
		without connecting TV/Monitor;			
		Input resolution up to 1080p			
		(50/60Hz), 1.3 HDMI, 3D			
		Supports 24 bit /deep color 30bit,			
		36bit per channel (36bit all channel)			
		deep color; Supports HDCP, Video			
		EDID Pass Through, Audio EDID			
		Settings: Pass, 2CH and			
		5.1CH.Does not support ARC.			
		HDMI resolution :			
		1080P/1080i/720p/576p/576i/480p/			<i>V</i> <sub>1</sub>
		480i			
		Operating Humidity range 5 to     Ook Bu (No Condensation)			
		90%RH (No Condensation)			
		Features :			
		Easy to install     High and the and assess the little in			
- 1		2. High quality and compatibility in			
		Product Category			
		Supports Apple TV and various			
		Blu-ray player			
		4. One HDMI input converted to			
1		one HDMI+ Audio		1 1	
		(SPDIF+R/L)output			
1		5. Output audio support :			4
		SPDIF+R/L analog Audio Output.			
		6. SPDIF output : support 5.1CH		~ 1	
		audio including Dolby Digital 5.1CH			
		and DTS 5.1CH(it does NOT			
		support Dolby Digital Plus and			
		PCM 5.1CH and beyond)			
		7. Input Resolution : up to			
		1080P(50/60Hz)/720P/480P			
		8. LED indication			
		9. Power supply : DC 5V/1AM			
		Specifications:			
		1. HDMI resolution:			
		1080P/1080i/720p/576p/576i/480p/			
		480i			
					*
		2. Support video color format:			*
		24bit/deep color 30bit,36bit			
		3. Audio output: L/R+SPDIF		8	
	0.000	4. Max bandwidth 225MHz			
- 4	PLS PULL	<ol><li>Max baud rate 6.75Gbps</li></ol>			
	G.			11,27	

		6. Input/Output TMDS signal		72	
		0.5~1.5Volts p-p(TTL)			
		7. Input/Output DDC signal 5Volts			
		p-p (TTL)			
		8. Input cable distance. & le; 15m			
		AWG26 HDMI standard cable			ki, 97 - 5'2
		9.Output cable distance ≤ 20m			
	3.7	AWG26 HDMI standard cable			
		10. Max working current: 500mA			
		11. Power adapter format Input:			
		AC (50HZ, 60HZ) 100V-240V;			
	10.0	Output : DC5V/1A			
		12. Operating Temperature range (-15 to +55;æ)			
	N <sub>4</sub>	13. Operating Humidity range 5 to			
		90%RH (No Condensation)			
		14. Dimension: 84X61.8X20mm (L			
		x W x H)			
		Operating and Connecting :			
	1.2	1. To use one HDMI cable to			
	1.3	connect the HD Source with the			
		input HDMI port.			
		2. To connect the converter HDMI			
		output port with the HD Display			
	in the	3. To use one audio cable to			
	7	connect the converter R/L port with			
		the audio equipment.			
	4.5	4. To use the optical cable to			
		connect the SPDIF port with the			
		audio equipment.			
		5. To connect the converter with 5V			
		DC power adaptor			
		Package includes:			
	6.8	1 x HDMI Converter			
		1 x DC 5V Power Adaptor			
16	Battery Operated	- Capacity, min./max.: 6.35 / 6.35 mm	04-Nos.		
	3.6-Volt	- Perfect for driving in tight spaces and			
	Multipurpose Screwdriver	hard-to-reach areas			
	Screwariver	- Optional angle screw and torque			
		setting adaptor: For even more			
		applications. Magnetic bit holder			
		- Used for repairing tasks, mounting			
		photo frame or paintings, lifestyle			
1	1.3	and gifting			
	7.	- Insert or remove screws with the			
		forward and reverse function of the			1 1 1 1
		tool. You can also use the tool for			
		drilling up to 2 mm to create pilot			
		holes for screws.			
		- Package Contents: 11 bits, 1			
	1.7	adaptor, 1 drill bit(2mm) lithium ion			
	Top	rechargeable battery-docking station			
		base charger		*	
17	Temp. Control	SOLDERING STATION	03-Nos.		
	Soldering Station	-micro controller controlled and		4 6 - 10	
		adjustable temperature			
		-LED display	SOLYTECHNIC X (S)		
r		- Voltage ~ 220-240V AC.	6		
		- Power Con+sumption 60W	N/ NXX		
,		- Frequency: 50 Hz.	5/00/0		
			III JY 13		
		SOLDERING IRON with Soldering	2/ /=/		
			THE POST OF THE PO		- 21-
			My The same of the		-
			ANDUL	100	

		Stand				
- 1		- Voltage: 24V AC.				
		- Power: 60W Heat up rating 130W.				
		- Temperature: 50-480°C.				
3	Soldering & De-	- Heating Element: Ceramic heater,				
	soldering Station	Accurate and advanced temperature,	03-Nos.	Dispersion of the last section and		
	or agricon	control with micro controller technology	05-1105.			
		Soldering and de-soldering LCD				
9		display panel		-		
		Soldering				
		- Power consumption : approx 60 W				
		- Input voltage : 170 to 270 V				
		- Output Voltage : 24VAC				
- 1		- Temperature range : 180 to 480 °C				
		- Temp stability : ± 10°C				
		- Temp accuracy : ± 1°C of tolerance				
		at idling time		=		
		- Tip to ground potential : Under 2mv		-		
		- Tip to ground resistance : Under			1 -	
		20hms				
		De-soldering				
1		Power approx 70 Watts				
1		Input: 170 to 270 V AC				
		Output Voltage : 24VAC				
- 1		Temperature range : 180 to 480°C				
1		Pump: Diaphragm type Vacuum: 600				
		mm/H, High, Quality 24V DC Pump				
		with approx 4000 RPM	-			
		SMD Hot Air				
		Input Voltage : 220VAC				
		Power Consumption : approx 300				
		Watts				
		Air Pump: Diaphragm Type Capacity:				
		24 L/min				
		Hot Air temperature : 200 to 550 Temp				
		Accuracy : ± 1°C				
		Accessories				
		Control Unit –o1 with with LCD		1		
		Display				
		Soldering Iron 1 No				
		De-Soldering Iron 1 No				
		Combined Soldering & De-Soldering				
		Stand -1No.				
		SMD Hot Air Iron 1No				
		SMT Hot Tweezer Handle -1No.				
		SMD Hot Air Stand 1				
		Hot Tweezer Stand 1No Power Cord-1No 01.				
		Tool Box Primary Filter 15 No				
		secondary Filters5 Nos Silicon Washer Set -1 Set				
		Glass Tube1 No				
		Nozzle Cleaning Spring 1 No				
		Single hole Nozzle 1No.				
_	Hi-Power		03-Nos.			
9	Soldering Station	Voltage 170-230V  Max. power output approx 150W	00-1105.		1	
	with Solder					
	Feeder	Temperature range 50°C-550°C				
	i ceuei	Approx 150 Watt 24V Pencil				
	Δ.	Tip-to-ground resistance: < 2				
	and the second	LHT-F tip				
		Features SOLYTECHA				
-		reatures				
		realures	1		-22	
		S S S S S S S S S S S S S S S S S S S	)		22	-

		<ul> <li>Digitized pushbuttons for precise temperature control</li> <li>Solder Feed Length, Speed and Time Programming Switches</li> <li>Digital display for Temperature</li> <li>Soldering Pencil Stand</li> <li>150 Watt Soldering Pencil</li> <li>Finger Switch for Feeding desired length of Solder Wire at SET speed</li> <li>Solder Wire Feeding Assembly</li> </ul>		
		SUNDRIES & ACCESS	ORIES	
20	HDMI TO RCA (AV) VIDEO CONVERTER	Supports- NTSC and PAL Standard TV formats output	06- Nos.	
		660		
		Full HD 720 / 1080p UP Scaler Adapter Must Support NTSC and PAL Standard TV formats output Full HD 720 / 1080p UP-Scaler Adapter En-capsuled in Handy Portable Box Appx. Size 6.0 x 5.5 x 2.0 cm		
		Compatible for Devices – PC, Laptops, Computers, HDTV, STB Box, DVD, Speakers etc. Full HD 720 /1080p UP Scaler Adapter		
21	RCA (AV) to HDMI Converter	Full HD 720 /1080p UP Scaler Adapter	06- Nos.	
		Encapsuled in Handy Portable Box Appx. Size 4.0 x 6.5 x 6.5 cm.		
22	HDMI to DVI Cable	Supports Resolutions for – 800x600, 1024x768, 1280x1024, 1600x1200, 1920x1200 and 1080p for high resolution LCD and LED monitors	06- Nos.	
		Special Features— HDTV to DVI, HDMI to DVI converter, HDMI to DVI, DVI to HDMI Cable – 6 feet Compatible Devices— TV, Monitor, PC		
23	DVI - VGA CONVERTOR cum DVI - VGA ADAPTER	DVI to VGA M/F Adapter Video Resolution Support For – 800x600, 1024x768, 1280x1024, 1600x1200, and 1920x1080	O6-Nos.	
	27 10 7		-23-	

	THE REAL PROPERTY.						
							Ĭ.
				100			
		(Audio is not supported over DVI or DVI)					
		VGA)			1		
		Data Transfer =					
	24 HDMLTO	Samples per Second			4	1 1 1	
1	TOWN TO VA						-2
	Adapter	Supports Resolutions – 23 x 0.6 x 0.6 cm				1 2	
		1 .0000 [11]	06-			T	3
		including 720p and 1600x1200 for HD	Nos.				
	1	monitors or projectors			1		
							2
					. 4		
		0				- '	
		Compatible With More Devices :-	=		7		
		Apple TV, Smart TV Box and other					
		devices with HDMI interface					
		- PC, Laptop, Ultrabook,			2-		
1		Chromebook, Macbook			-		
		- Rasberry Pi, Streaming media					
25	USB-C to HDMI	player					
	Adapter	HDMI (4K@60Hz) VGA (1080P@60Hz)	06-				
	Maplet	Converter	Nos.				
		Supports Resolutions –	1403.				
		1080p FULL HD-up to 1920x1080					
		including /20p and 1600x1200 for HD					
		monitors or projectors					
1							
1							
		•			4		
		Dual Monitors Setup –				7- 2-	
		USBC to HDMI +VGA adapter to extend					
		or mirror screen of :-					
		Laptop / MacBook Pro, MacBook			100		
		Air iMac iPad Pro / U.D. Fila D					
		Air, iMac, iPad Pro / H P EliteBook /					
		Thinkpad Folio / Yoga / ChromBook - PC / Tablet to Projector / TV /			3		
		Monitor / Display					
		Monitor / Display					
		The HDMI and VGA port work simultaneously.					
		simultaneously,					
		- Can be used USB C - HDMI and				- 17	
		USB C - VGA at same time.					
		Compatible With More Devices :-					
		<ul> <li>Apple TV, Smart TV Box and other</li> </ul>					
	1	devices with HDMI interface					
		<ul> <li>PC Laptop, Ultrabook,</li> </ul>		1-			
		Chromebook, Macbook		1			
		<ul> <li>Tablet: Galaxy TabPro S, Tab S4,</li> </ul>					
		mode(S20/ S10/ S9/ S8/ NOTE 8/					
		NOTE9)			- V		
		Rasberry Pi, Streaming media			-		
		player etc.					
26	AT89S52				1 3		
	DEVELOPMENT	- AT89S52/53 Microcontroller based	03-		4		1 1 1 1 1
	BOARD	Compact and Ready to use design	Nos.				
	DOAND	<ul> <li>Professional EMI/RFI Compliant PCB</li> </ul>	STATE ASSESSED.				
				-			.4



		*	
	Layout Design for Noise Reduction		
	<ul> <li>High Quality Two layer PTH PC</li> </ul>		
3	<ul> <li>No Separate power adapter instead</li> </ul>		
	USB-Power Source  - Screw terminal for External power		
	Supply (with Jumper Select Option) /		
	Supply range of 7V to 20V / Adaptor		
	(any standard 9-12V power supply		
	option  With Power LED Indicator		
	- 1-Amp Voltage Regulator		
	<ul> <li>Power Supply Reverse Polarity</li> </ul>		
	Protection		
	RS-232 Interface (For direct connection to PC's serial port)		
	- On board		
	- 16-MHz Crystal Oscillator / 04-		
	Multiplexed 7-Segment LFD Display		
	<ul><li>02-Line LCD Display (2x16)</li><li>On board I2C EEPROM (4K-</li></ul>		
	AT24C04) / I2C RTC (DS 1307) with		
	Crystal (16-MHz Crystal Oscillator)		
	and Battery		
	<ul> <li>02-External Interrupts and Reset buttons / Buzzer / Relay Interface</li> </ul>		
. 11 72 1	<ul> <li>Matrix keyboard (12 keys) / Pull-Up</li> </ul>		
	(4 Keys) Keyboard / IR Sensor		
	Interface - TSOP 1738 / 8-LED		
	Interface to test I/O  On board DB-9 and USB / JTAG,		
	ISP, All Port Pins available at IDC		
	(2x5) Connector		
	<ul> <li>AT89S52/53 Development board Software CDROM with</li> </ul>		
	Schematic, Programming		
	Software, Sample Hex Code and		
EVALUATION	Example Codes		
BOARD FOR WI-FI	Board used for Wi-Fi connectivity via Serial Host Interface	03-	
SOARD FOR WILL	Quick Booting Time : under 20-milli-	Nos.	
	sec		
	<ul> <li>Ultra Low Power through Dynamic</li> </ul>		
	Power Management (34µA at the		
	Standby mode)  Operates with standard 802.11b/g/n		
	access point at speed up to 11Mbps		
	(802.11b)		
	- Security Protocol : WEP,		
	WPAWPA2-PSK, Enterprise EAP-		
	FAST, EAP-TLS, EAP-TTLS, PEAP		
	<ul> <li>Operation Temperature : -40°C ~</li> <li>85°C</li> </ul>		
	Board Size - Compact Size : Appx. 32 x		
9 9 1	24 x 3 (mm)		
	- CE, FCC, KCC Certified		
	ACCESSORIES		
	- Evaluation Board	CIPIO	
	<ul> <li>Wi-Fi 220 Modules on Breakout- Board</li> </ul>	CAT GIALS D	c. \
	- USB Cable	THE GIRLS	1/2
	- RS232 Serial Cable	The state of the s	10
	Ť	13107	18/-25-
		181.	3/

	-				
.8	1	• 48 10/100/1000BASE-TX			
0		2 1000BASE-TX	04		
1	Layer-2 Switch	• 2 Combo			
1	-ayer 2 Switch	10/100/10000			
		10/100/1000BASE-T/100/1000SFP			
		Capacity - 130 Chas			
		16MB		,	
		Managed			
		SENSOR TYPE-1/2 5 type /2 30 mm)		S. A.	
		mullinated Eymor Pa CNACE			
		3611301			
		EFFECTIVE PIXELS (VIDEO)- approx. 8.29			4
		iviegapixels (16:9)²			
		• IMAGE PROCESSOR- BIONZ X™ image			7
		processor			
		<ul> <li>LENS TYPE- ZEISS Vario-Sonnar ® T*</li> </ul>		7	
		• FILTER DIAMETER-55 mm			
		Lens cover- Auto			
29	Video Handy cam	• Aperture- F 2.0 - 3.8	01 Set		
-5		• Focal distance-4.4 to 88 mm		4	
		Optical 200111- 20X			
		Optical Image zoom- 4K: 30x, HD: 40x			
		SCREEN TYPE-7.5 cm (3.0 type) Clear			
		Photo LCD display (460,800 dots) Wide			
		(16:9)			
		<ul> <li>IMAGE STABILIZATION TYPE- Balanced</li> </ul>			
		Optical Steady Shot w/ Intelligent Active			
		mode (5-axis)			
		FOCUS TYPE-Contrast AF			
		AUTO CONTROL RANGE-1/6-1/10000			
		• STANDARD-1/50-1/10000			
		MANUAL IRIS CONTROL (PHOTO		•	
		MODE)-1/25-1/10000		1	
		MEDIA TYPE-XAVC S 4K (100 Mbps):			
		SDHC Memory Card (4 GB or over, UHS-I			
		U3 or Higher) / SDXC Memory Card			
		(UHS-I U3 or higher)			
		RECORDING FORMAT (VIDEO)-XAVC S			
		format: MPEG4-AVC / H.264, AVCHD			
		format ver. 2.0 compatible: MPEG4-AVC			
		/ H.264, MP4: MPEG-4 AVC / H.264			
		VIDEO RESOLUTION-XAVC S 4K: 3840 x	-		
		2160 / 25p, 24p, XAVC S HD: 1920 x			
		1080 / 50p, 25p, 24p, AVCHD: 1920 x			
		1080 / 50p (PS), 25p (FX, FH), 24p (FX,			
		FH), 50i (FX, FH), 1440 x 1080 / 50i (HQ,			
		LP), MP4: 1280 x 720 / 25p			
		VIDEO RECORDING RATE (ABR / VBR)-			
		XAVC S 4K: approx. 100 Mbps, XAVC S	-		
		4K: approx. 60 Mbps, XAVC S HD:			
		approx. 50 Mbps, AVCHD PS: approx. 28			
		Mbps / FX: approx. 24 Mbps / FH:			
		approx. 17 Mbps / HQ: approx. 9 Mbps /			
		LP: approx. 5 Mbps, MP4: approx. 3			i 5
		Mbps			
		RECORDING FORMAT (STILL IMAGE)-			
		JPEG (DCF Ver. 2.0 compatible, Exif Ver.	<b>10</b>		
		2.3 compatible, MPF Baseline	1	GIRLS	7 = 3
		2.5 compatible, wirr baseline	1	The state of the s	

Main (C.G.)

		compatible)  STILL IMAGE SIZE (PHOTO MODE)- L: 16.6 Megapixels 16:9 (5440 x 3056), 12.5 Megapixels 4:3 (4080 x 3056), M: 8.3 Megapixels 16:9, (3840 x 2160), 6.2 Megapixels 4:3 (2880 x 2160), S: 2.1 Megapixels 16:9 (1920 x 1080), 0.3 Megapixels 4:3 (640 x 480)  MICROPHONE- Built-in Zoom Microphone  AUDIO RECORDING FORMAT- LPCM 2ch (48 kHz / 16 bit) <sup>13</sup> , Dolby Digital 5.1ch, Dolby Digital 5.1 Creator 14, Dolby Digital 2ch Stereo, Dolby Digital Stereo Creator 14, MPEG-4 AAC-LC 2ch  WI-FI- IEEE 802.11 b/g/n (2.4 GHz band) NFC-NFC forum Type 3 Tag compatible			
30	Headphone with built in Mic (Professional)	<ul> <li>Impedance-24 ohm</li> <li>Supports Stereo Sound</li> <li>Sensitivity-102 dB</li> <li>Response bandwidth- 5 - 22000 Hz</li> <li>Speaker Driver Unit- 30 mm</li> <li>Microphone Type- Built-in</li> <li>Plug Type- L-shaped gold-plated 4-pole mini plug</li> <li>Headphone Driver- 30 mm Dome</li> <li>Type Driver</li> </ul>	30 Set		



## Group – B Department - Architecture & Interior Decoration And Design

ी. मशीन	PRICE-E	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	main o thanka Malana al agus phallagairtí a ná thai a phillipeantair air ga		
नशान उपकरण क	स्पेशिफिकेशन	मात्रा	दर (जीएसटी सहित)	राशि	रिमार्क.
Potter's wheel	Power- 1/3 HP (1440 RPM) Size- 600 mm X 600 mm X 350 mm Wheel- 300 mm (Overall diameter) Drive- Motor cone attached	02			
3D Printer pen Doodler	Operator-One(Unskilled)  3D Printer Pen Doodler Scribbler Modelling PCL & PLA Power Bank 5th Generation Pen 10M PCL Safe Finger Cap kids safe low temperature	03			
Melting Furnace	<ul> <li>Product Dimensions: 22.9 x 22.9 x 44.4 cm</li> <li>Microprocessor Based Pid Temperature Control</li> <li>Metal Melting Furnace 1Kg metal Capacity</li> <li>Maximum Temperature 1200 C</li> </ul>	02			
Rectangular Muffle Furnace	<ul> <li>Three Phase Size         150x150x300 mm Temp         Range 1450°C by mLabs</li> <li>Light Weight With Ceramic         Fiber Wool Insulation         (instead Of Brick         Insulation). The Outer         Casing Is Made Of Double         Walled Thick P.c.r.c. Sheet         Duly Powder Coated.         Heating Elements Are         Made Of Kanthal 'a-1" Wire         &amp; Backed By High Temp.         Insulation Which Avoids         Loss Of Energy. Temp.         Control Unit Consists         Microprocessor Digital         Temp. Controller Fitted In         Front Of Furnace With Two         Pilot Lamps. The Apparatus         Is Complete With         Thermacle Fitted With         Thermacle Fitted With         Thermacle Fitted With         Thermacle With         Thermacle With         Thermacle Fitted With         Thermacle With         Thermacle With         Thermacle Fitted         With Power Plug. To Work         On 220/230 Volts Or         400/440 Volts A.c.         Maximum Temp. Is 1000°c         &amp; Working Temp. 950°c.         For Model Of Higher</li> </ul>	01	SOLVICANO X		

		Temp. The Maximum Temp. Is 1200°c, 1450°c & Working Temp. 1150°c & 1400°c.				
5. On the second of the second	Circular saw	<ul> <li>Rated power input- 1,100 W</li> <li>No-load speed 5.200 rpm</li> <li>Weight 3.6 kg</li> <li>Saw blade bore diameter 20 mm</li> <li>Saw blade diameter 184 mm</li> <li>Cutting depth</li> <li>Cutting depth (90°) 65 mm</li> <li>Cutting depth (45°) 47 mm</li> </ul>	02			
6.	Table saw machine	<ul> <li>WEIGHT 26.0000</li> <li>VOLTAGE 220v-240v, Single phase, A/c</li> <li>POWER INPUT 1800W</li> <li>SPEED 3.200 rpm</li> <li>BLADE DIAMETER 254 mm</li> <li>BLADE BORE 25.4 mm</li> <li>MLTER CAPACITY [RIGHT/LEFT] 460MM/210MM</li> <li>NO LOAD SPEED 3650 RPM</li> <li>BEVEL CUT Incline setting: 47 ° L / 2 ° R</li> <li>LENGTH X HEIGHT Table size: 642 x</li> <li>572 mm</li> </ul>	01			
- Company (Application of the Company of the Comp	Scroll saw	This is the perfect machine for tool and die making model building toy repairs puzzle sawing architectural work antique restoration etc. It operates problem-free even when cutting acrylics fiberglass polystyrene foams rubber leather and cork. super cutting capacity (wood 1 1/2 plastics 1 3/16 nonferrous metals 25/64) air blower with adjustable nozzle unit's machine base of cast iron, vibration-free operation. aluminum die-cast table tilt up to 45°.  5 coarse and 5 fine saw blades	02	POLYTECK!	wick of	

		Start				
	1	Stroke length 3/4 Table Size 14 1/4 x 7 3/32 (tilts up to 45% formal size 14 1/4)				
		x 7 3/32 (tilts up to 45° for miter cuts) Throat Depth 15 3/4 (1886)				
		cuts) Throat Depth 15 3/4 (400 mm) Cut Depth 1 1/2 (1 at 45° table with				
		Cut Depth 1 1/2 (1 at 45° table tilt)  Overall measurements 1				
		Overall measure (at 45 table tilt)				
		55/64) Width (11 1/32) Height 11 13/16 Volts 110-120V A Community				
		13/16 Volts 110-120V AC 60 Hz Weight 44 lb				
8.	IRON JACK	Weight 44 lb.				4
	PLANE	• Size 14"				
	LANE	• Plane/Comment	03			
		Plane/Corrugated Base     Professional Vision				
		Professional Wood     Worker's Plainer				
		Wooden Grip				
		• Cast Iron Dad				
		Cast Iron Body				
9.	IRON JACK	• Size 10"				
	PLANE		03			
		Plane/Corrugated Base				
		Professional Wood				
		Worker's Plainer				
		Wooden Grip				
		Cast Iron Body				
10.	Multitool Nail	Multi to al N. II Co. II C	0.5			
	Staple Gun and	Multi tool Nail Staple Gun	03	4		
	rivet gun	Furniture Stapler For Wood Door				
	Tivet guii	Upholstery Framing Rivet Gun Kit		* = 2*		2
		Size: approx.107 mm x 155 mm Net				
		Weight:approx.780 g/set (with case)				
		Features: 1.No need for electricity				
		or air;				
		2. Three nail types: T style, N style,				
		U style.				
		1 x staple gun 1 x 5/16"staples 1 x				
		1/2"staples Power				
		Size:107mmx155mm		= =		
11.	Digital SLR	Digital SLR Body with 18-55mm	01			
11.	Camera	VR Kit Lens and 55-200mm Lens,	01			4
	Callicia	BS-1 Accessory Shoe Cover, DK-				7 1
		25 Rubber Eyecup, BF-1B Body				
		Cap, EN-EL14a Rechargeable Li-				
		ion Battery (with terminal cover),				
		MH-24 Battery Charger, AN-DC3				
		Strap, UC-E17 USB Cable, EG-			1	
		CP16 Audio/Video Cable, DK-5		* AL -		
		Eyepiece Cap, ViewNX 2 CD,				
		Reference CD (contains the			- F	1 3
		Reference Manual), 8GB Card and				
12	Combination	Camera Bag	0.1			
12.	Graphical pen	Product 20 x 16 x 0.88	01			
	tablet for pc	Dimensio cm; 250				
		ns Grams				
		Grains				
		Batteries 1 Lithium ion				3
		batteries				1
		manipad	No. of Concession, Name of Street, or other Persons, Name of Street, or ot	May no see the second		
			2150	STATE!		
		i s	21	man 18	1	
		Į Ø	1-	- NA 5		
		A to	1	1 *		-30-
		i di	1	18		3
			A. C.	151		
			Ja. Wasser.	and the same of th		
		A.	VAn.	K FREITS		
anne de la		***	A STATE OF THE PARTY OF THE PAR	N. C.		

S. Francisco (S.C.)	CNC 3d Printer and cutter (CNC	Connectiv ity technolog ies  Other display features  Colour H  Whats in the box H  CNC Wood heave	Personal Computer  Black One pen tablet, pen, Replacement Nibs, USB Cable, Quick start guide  y duty carving				
Statement and the second secon	and cutter (CNC	Other display of features  Colour II  Whats in the box II  CNC Wood heave	Computer  Black  One pen tablet, pen, Replacement Nibs, USB Cable, Quick start guide				
Statement and the second secon	and cutter (CNC	Whats in the box I	One pen tablet, pen, Replacement Nibs, USB Cable, Quick start guide				
Statement and the second secon	and cutter (CNC	the box	pen, Replacement Nibs, USB Cable, Quick start guide				
Statement and the second secon	and cutter (CNC		y duty carving				
The state of the s		N. C L	, , .	01			
10 miles (10 miles)	Wood heavy duty	Fully Automatic	nation Grade:				
	carving Machine, Automation Grade: Fully	Automation Grade Frequency	Fully Automatic 50 Hz				
100	Automatic)	Phase	3 Phase				
22		Voltage	415 V				
현 60명을 한다는 한다는 한 10명을 하는 것		Power Source Maximum Tool Diameter Spindle Type	Electric Upto 20 mm Air Cooled				
		Spindle Speed	24000 RPM				
3		Spindle Power	5 KW				
and the second of the second s		Maximum Traverse Rate Outer Dimension X Axis Travel	10000 mm/minute 2000x3000 mm 1300 mm				
		Y Axis Travel	2500 mm				
		Z Axis Travel	200 mm				
		Axis Slider	25 mm HIWIN Linear motion guide				
14.	Total station	Telescope		01	1	1	
		Resolving power Others	30x / 2.5"  Length: 171mm (6.7in.), Objective aperture: 45mm (1.8in.) (48mm (1.9in.) for EDM),		RISPOLY		

		of view: 1°30'
		(26m/1,000m)
		Minimum focus: 1.3m (4.3ft.) Reticle
		illumination: 5
Angle me	easurement	brightness levels
MinImum	Display	0.5"/1"
		(0.0001 / 0.0002gon,
Accuracy	(70.0	0.002 / 0.005mil)
_1/123-3	:2001)	1"
Dual-axi	S	Dual-axis liquid tilt
compens	Sator	sensor, working
Collimati	ion	range: ±6' On/Off (selectable)
compens	sation	
Laser ou	measurem	
	срац.	Reflectorless mode : Class 3R /
		Prism/sheet mode :
Measu	Reflecto	Class 1 0.3 to 800m
ring	rless.	(2,620ft.) / Under
range (under		good conditions:: 1,000m (3,280ft.)
averag	Reflecti	RS90N-K: 1.3 to
е	ve	500m (4.3 to
conditi ons <sup>2</sup> )	sheet.	1,640ft.), RS50N-K: 1.3 to 300m (4.3 to
0.15		980ft.),
		RS10N-K: 1.3 to
	Mini	100m (4.3 to 320ft.) CP01: 1.3 to 2,500m
	prisms	(4.3 to 8,200ft.),
		OR1PA: 1.3 to 500m
	One	(4.3 to 1,640ft.) 1.3 to 5,000m (4.3
	prism	to 16,400ft.) / Under
	,	good conditions: : 6,000m (19,680ft.)
Minimun	n Display	Fine / Rapid :
		0.0001m (0.001ft. /
		1/16 in.) / 0.001m (0.005ft. / 1/8 in.)
		(selectable)
		Tracking / Road : 0.001m (0.005ft. /
		1/8 in.) / 0.01m
		(0.02ft. / 1/2 in.)
Accura	Reflecto	(selectable) (2 + 2ppm x D) mm
CA.1	rless"	
(ISO	Reflecti	(2 + 2ppm x D) mm
17123	ve sheet	
4:200	Prism"	(1.5 + 2ppm x D)
1)		mm
(D=m easuri		
ng		
distan		
ce in mm)		
Measu	Fine	0.9s (initial 1.5s)
ring	Rapid	0.6s (initial 1.3s)
time ** Tracking		0.4s (initial 1.3s)
OS, Inte	rface and D	ata management
Operatin	g system	Linux
Display /		Graphic LCD, 192 x 80 dots, backlight,
Keyboard	u	contrast adjustment
		/ Alphanumeric
		keyboard / 28 keys
Control	anel	with backlight On both faces
Control p	Jailei	Oil both faces
Trigger k	ey	Yes (right side)
Data	Internal	Approx. 50,000

OF THE PARTY OF TH

	storag memor y Plug-In memor y device Interfa ce  Bluetoo th modem (option)  General Guide light  Laser-pointer  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser (option)	USB flash memory (max. 32GB)  Serial RS-232C, USB2.0 (Type A for USB flash memory) Bluetooth Class 1.5, Operating range: up to 10mm  Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm), Ream accuracy:					
	Interface  Bluetoo th modem (option)  General  Guide light  Laser-pointer  Levels  Graphic  Circular level (on tribrach)  Plumm Optical et  Laser	(max. 32GB)  Serial RS-232C, USB2.0 (Type A for USB flash memory) Bluetooth Class 1.5, Operating range: up to 10m.  Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Interfa ce  Bluetoo th modem (option)  General  Guide light   Laser-pointer   Levels Graphic Circular level (on tribrach )  Plumm Optical et  Laser	USB2.0 (Type A for USB flash memory) Bluetooth Class 1.5, Operating range: up to 10mm  Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Interface  Bluetoo th modem (option)  General Guide light  Laser-pointer  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	USB2.0 (Type A for USB flash memory) Bluetooth Class 1.5, Operating range: up to 10mm  Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Bluetoo th modem (option)  General Guide light "  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	th modem (option)  General Guide light a  Laser-pointer a  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	Bluetooth Class 1.5, Operating range: up to 10m.  Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	General Guide light  Laser-pointer  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Ceneral Guide light  Laser-pointer  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	Green LED (524nm) and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	General Guide light "  Laser-pointer"  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Laser-pointer  Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	and Red LED (626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	(626nm), Operating range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	range: 1.3 to 150m (4.3 to 490ft.) Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	Coaxial red laser using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Levels Graphic Circular level (on tribrach ) Plumm Optical et  Laser	using EDM beam 6' (Inner Circle) 10' / 2mm  Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Circular level (on tribrach ) Plumm Optical et	Magnification: 3x, Minimum focus: 0.5m (19.7ln.) from tribrach bottom Red laser diode (635nm±10nm),					
	level (on tribrach ) Plumm Optical et	Magnification: 3x, Minimum focus: 0.5m (19.7in.) from tribrach bottom Red laser diode (635nm±10nm),					
	Plumm Optical et	Minimum focus: 0.5m (19.7ln.) from tribrach bottom Red laser diode (635nm±10nm),					
	Plumm Optical et	Minimum focus: 0.5m (19.7ln.) from tribrach bottom Red laser diode (635nm±10nm),				ı	
	et	Minimum focus: 0.5m (19.7ln.) from tribrach bottom Red laser diode (635nm±10nm),			1		
	Laser	0.5m (19.7ln.) from tribrach bottom Red laser diode (635nm±10nm),					
		ribrach bottom  Red laser diode (635nm±10nm),					
		(635nm±10nm),					
	(Option)						
		Beam accuracy:					
		<=1.0mm@1.3m, Class 2 laser product					
	Dust and water	IP66 (IEC					
	protection /	60529:2001) / -20 to					
	Operating temperature	+60°C (-4 to +140°F)					
7 A.	Size with handle	183(W)x 181(D)x					
	Instrument height	348(H)mm			- ,		
	- Indigite	92.5mm from					
		tribrach mounting surface					
	Weight with	Approx. 5.3kg					
	battery & tribrach	(11.7lb)					
	Power supply Battery	Li-ion rechargeable					
		battery BDC70					
	Operating time (20°C)	BDC70: Approx. 28hours:					
	Application program		× .				
	On board	REM Measurement					
		3D Coordinate     Measurement					
		Resection					
		<ul><li>Stake Out</li><li>Topography</li></ul>			=		
		Observation			2 2 2		
		Offset     Measurement					
		Measurement     Missing Line					
		Measurement					
	1 1	Calculation					
		Route Surveying     Point to Line					
ser Measuring	Measurement	working a distribution on the following and sold actions of sometimes	05				
pe							
		625 1	-	. 6 40			
	Laser diode	655 nm, < 1	A TON	ALD POLL	1 1		
7.1.		m W	1 70	The state of the s	1		
	Measurement	0.05 - 50.00	13/	(N)	1 2		
	1 ' '	m			3		
	1		171		101		
			to gran the				
			1 1 1	in Raion	07/		- 33 —
	er Measuring e		Observation Offset Measurement Missing Line Measurement Intersection Surface Area Calculation Route Surveying Point to Line  Measurement  Measurement  < 0.5 s	Observation Offset Measurement Measurement Intersection Surface Area Calculation Route Surveying Point to Line  er Measurement time, typical  Laser diode  Measurement Tange  O.05 – 50.00 Measurement Tange  Omega  Observation Osservation Measurement O.05 s Osservation Os	Observation Offset Measurement Missing Line Measurement Intersection Surface Area Calculation Route Surveying Point to Line  er Measurement time, typical  Laser diode  Measurement The mw  Measurement The mw	Observation Offset Measurement Measurement Intersection Surface Area Calculation Route Surveying Point to Line  er Measurement time, typical  Laser diode  Measurement Tange  Measurement Measurement Measurement Tange  O.05 - 50.00 Measurement Tange  Observation Offset Measurement Me	Observation Offset Measurement Measurement Measurement Intersection Surface Area Calculation Route Surveying Point to Line  er Measurement time, typical Laser diode Measurement mW  Measurement range m  Observation Observation Measurement Measurement Measurement mW  Measurement Tange Measurement Measuremen

	Laser class	2				
	Measurement accuracy, typical	± 1.5 mm* (*plus usedependent deviation)				
	Measurement range of incline	0 – 360° (4 x 90°)		E F :		
	measurement Measuring	0.004				
	accuracy (typical)	± 0.2°* (*plus use-dependent deviation)				
*	Measurement time, max.	4 s				
	Power supply	2 x 1.5 V LR03 (AAA)				
	Automatic deactivation	5 min				
	Weight, approx.	0.1 kg				
	Units of measurement	m/cm, ft/inch			ξ ‡	
	Memory capacity (values)	20				
	Battery lifetime, individual measurements, approx.	10,000				
	Battery lifetime, operating time, approx.	2.5 h				
	Dust and splash protection	IP 54				
	Tripod thread	1/4"				
	Laser colour	Red				
	Measuring range, up to	50 m			2	2
Carpentry lab Machine	Multipurpose Woodworking Machine		01			
L			1	 		



16.

Weight (net)	550 kg				
Tension	230 V Mono / 400 V Drehstro m – 3phase				
Versions					
250 mm	mit Vorritz / with scoring unit				
315 mm	ohne Vorritz / without scoring unit				
Saw					
R.p.m.	4500				
Diameter saw blade and bore	250 x 30 mm / 315 x 30 mm				
Diameter scoring saw blade and bore	100 x 20 mm				
Cutting depth at 90°	85 mm (250 mm) / 107 mm (315)				
Cutting depth at 45°	55 mm				
Dimensions cast iron table	1080 x 410 mm				
Length sliding table	1450 x 320 mm				
Cutting length	1650 mm	10	LSPOUR	wh.	

	Cutting	800 mm			
1	width	ooo mm			
	parallel fence				
,					
	Motor	5 PS/hp			
	power	0 1 3/np			
17. Wood Turning				Service Colonia Similar Schedulin (Colonia Schedulin Street)	71 19
Lathe Machine					
	D				
	Product		01		
	Specification Usage/Applic				
	tion	a Wood turning			
	Material	cast iron bed			
	Power	550W 1Ph			
		230V 50Hz			
	Motor	induction			
	Automation	1400rpm			
	Grade	Semi- Automatic			W. S. S.
	Machine	510mm centre			
	Capacity	distance			
	Minimum	1			
	Order Quantity	/			
	Product				
	Description SPECIFICATI				
	ONS				
	Voltage, V	230			
	Power	0.55			
	consumption, kW				
	Swing	230 mm			
	diameter over	230 mm			
	support			6	
	Swing	305			
	diameter over bed, mm		*		
	Distance	510			
	between	510	,		
	centers, mm				
	Extension of	545 mm			
	the bed	(optional)			
	Spindle taper	MK-2			
	Spindle thread	M33 x 3.5			
	Tailstock taper	MK-2			
	Tailstock quill	50			
	stroke, mm	50			
	Length mm	860			
		000	A Part of the last		
		CHINER	GIRLS P	CA TO THE WAY	 36—
			N. C.	1	

Width, mm	270	
Height, mm	410	
Weight, kg	28	



# Group – C

# **Department - Modern Office Management**

P	RIC	-		n	
UL	216	-	_	ĸ	
			_		

	PRICE - DID						
स.क.	मशीन उपकरण का नाम	स्पेशिफिकेशन	मात्रा	दर (जीएसटी सहित)	राशि	रिमार्क	
1	Bar Code reader (For Student Training Purpose)	<ul> <li>58mm maintenance free         USB Thermal Printer for         Fast Printing</li> <li>Infinity iBill Lite GST         Software for Invoicing,         Inventory and Barcode         Label Printing</li> <li>Software Supports Laser,         Inkjet, Thermal and         Barcode Printers</li> <li>Tvs Barcode Reader for         high speed scanning</li> </ul>	01				
2	Paper Cutting Machine (For Student Training Purpose)	• Gold Leap 12" गिलोटिन पेपर कटर, A4 द्रिमर, 400 Sheet Capacity गिलोटिन	01				
3	Sealing Machine (For Student Training Purpose)	• Royal 6" हैड इंपल्स हीट सिलिंग मशीन 2 एलिमेंट, Teflon Cloth 16" मटेल आरेंज	01				
4	Automatic Letter Opener Machine (For Student Training Purpose)	Martin Yale my 1628     Desktop Electric Letter     Opener	01			-	
5	Heavy Duty Stapler (For Student Training Purpose)	<ul> <li>Stapler Unboxing FL 12</li> <li>M24 (300 Page Stapler Capacity)</li> </ul>	01				
5	Paper Punching Machine (For Student Training Purpose)	• DP. 800 Page	01				
7	Vaccum Cleaner (For Student Training Purpose)	<ul> <li>Multi Purpose wet &amp; dry ,Vaccum cleaner with Power ful blower &amp; suction function,suction power, 1800 mm of water column, Input power 1150 w.</li> </ul>	01				
3	Paper Shredder M/c (For Student Training Purpose)	Automatic cross cut Fellowes office Paper shredder m/c, output paper size 4X38 mm	01				
	Spiral Binding M/c (For Student Training Purpose)	Dotpot Spiral Binding Machine A/4 , 14-16 70 GSM & 40 Hol Sheet, Havey Duty	01				



10 Thomas Inc.	machine White			
Thermal Binding Machine (For Student Training Purpose)	Iron Thermal Binding SK 5000(A4) Max Binding Sheet width 200- 300mm	01		
Plastic Comb Binding M/c (For Student Training Purpose)	C1S Comb binding machine, Capacity 500 Sheets	01		
12 Tripod	Unifree WT-330A एल्युमिनियम पोर्टेबल ट्राईपॉड •स्टेंड 3 वे हेड डिजीटल कैमरा कैमकार्डर के लिए मोबाइल होल्डर ट्राईपॉड किट के साथ (3000 g तक	04		



# Group – D Department - Costume Design and Dress Making PRICE - BID

स.क.	मशीन उपकरण का नाम	स्पेशिफिकेशन	मात्रा	दर (जीएसटी सहित)	राशि	रिमार्क
	DRESS FORM WITH ARM     Style: Universal     Colour: Black/	Female Dress Form:  1. Size-6:  Chest-32.5  Waist-23.5	01	7		
1	Skin  Fully pin-able form  4 wheel heavy metal adjustable stand	<ul> <li>Hip- 34.5</li> <li>Size-8:</li> <li>Chest-34.5</li> <li>Waist-25.5</li> <li>Hip- 36.5</li> </ul>	01			
		Girls' Dress Form:  1. Size: 8 Years	01			
	Male Dress Form:  1. Size: 40  • Chest-40  • Waist-34  • Hip- 41	01			-	
	MANNEQUIN	Female mannequin  • Size: Standard	02			
	<ul><li>Fiber Body</li><li>Metal Stand</li><li>Hair wig</li></ul>	Male mannequin  • Size: Standard	02			
2	<ul><li>Colour: Skin</li><li>Detachable</li><li>Mannequin</li></ul>	Boy mannequin  Size: 6 yr Size: 8 yr	01 01			V-
	<ul> <li>Dummy consists of a head, a torso, 2 arms, 2 legs and metal stand.</li> </ul>	<ul><li>Girl mannequin</li><li>Size: 6 yr</li><li>Size: 8 yr</li></ul>	01 01			
3	Folding Stand For Dress Hanging	<ul><li>Material: Steel</li><li>Size: 4½'</li></ul>	24			
4 ,	Automatic Electric Iron	<ul> <li>19 Steam Vents With 5 Fabric Settings</li> <li>Ceramic Coated Non – Stick Soleplate</li> <li>1300 Watt effective performance</li> <li>Powerful Steam Output of up to 18 gm / minute</li> <li>180 ml Large Water Tank Capacity</li> <li>2 Year Warranty</li> </ul>	10	SPOLL		

A Rejou Co

5	Cloth Isania T. I.				and the second s		
3	Cloth Ironing Table	•	Size: 4'x 2'x 3' (LxBxH)	04			
			Material: Wood/ Metal				
,			Foldable Ironing Board with				
	-4		Iron stand				
			Heat Resistant Iron holder				
	l l l l l l l l l l l l l l l l l l l	•	Aluminized Cloth cover				



# Group-E Department- Pharmacy PRICE-BID

ा.क.	मशीन उपकरण का नाम	स्पेशिफिकेशन	मात्रा	दर (जीएसटी सहित)	राशि	रिमार्क
1	Melting point Apparatus	Capillary Type with window	2-Set			
2	Student organ bath	Stainless steel body, Size 12x9x8 inch	1-Set			
3	Digital Water Bath	Stainless steel body, 3 liter, Digital temperature control	1-Set			
4	Dissolution Test Apparatus	Single Station Temp Control, IP grade	1-Set			
5	Sonicator	Bath Type, Steel Made, 1500 Watt, 3 Liter	1-Set			
6	Blood Pressure Apparatus	Sphygnomanometer Mercury Type	1-Set			
7	Hot plate	Digital, Temp 0-250 Degree C	1-Set			
8	Tablet Hardness Tester	Phizer Type	1-Nos			2



## Group - F

## Language Lab

## PRICE-BID

S. No	List of Equipment	Specification	Quan	Rate	Amount	Remark
S. No	List of Equipment  Digital Language Lab software (English)	<ul> <li>SOFTWARE LICENCED (Perpetual)         SPECIFICATION FOR     </li> <li>The software should be based on the parameters as defined by the ALTE&amp;CEFR for language framework</li> <li>It should be Window 32bit &amp; 64bit both supported software.</li> <li>License user terminals: License to be provided for1 teacher console and 30 student users</li> <li>The software should be designed &amp; developed using WEB2 technologies and operational on all major operating systems.</li> <li>License: It should be life-time perpetual license.</li> <li>Secured login: The main interface of the teacher with password protected</li> </ul>	Quan tity  01 Set	Rate	Amount	Remark
		<ul> <li>FUNCTIONALITY SPECIFICATION *         <ul> <li>Learner Activity monitoring through Teacher dashboard</li> <li>Incognito listening—in student module.</li> <li>Intercom: Two-way intercom communication between teacher &amp;student, through text, audio &amp;video.</li> <li>The software should have Sample lessons for words and pronunciation.</li> <li>The software should have Lesson Plans with focus on expression and comprehension.</li> <li>Student material: Material in the</li> </ul> </li> </ul>				

GIRLS POLLTRICHNIC - 43

- form of E-Books for each level should be available. This material should be integrated as whole.
- Resource material &training: Training on usage of the language lab software to all the teachers. Proper detailed training material to be provided for each level as the delivery mechanism.
- The software should create independent students group.
- Pairing of students for interactive session
- The software must have facility to conduct online exam with one answer, multiple answer, alternative and easy type.
- Screen Records (with A/v and Marker Tool Marks) transfer facility between all members and teacher
- Facility to broadcast voice and screen of Master Computer (Teacher console).
- The software must have facility of Real time lesson editing and lesson reassigning
- It should support Interactive online activities
- Multi accent training
- Webpage Control Features
- Graphical representation of voice waves
- Recap Functionality.
- Model imitation.
- Student activity logging facility.
   Student should be able to create any bookmark on audio
- Voice Insert between speech facilities.
- Pronounce module. Should provide solutions for improving oral skills and allow to transform text material into spoken audio for pronunciation and speech practice.
- The software must have the facility to create assignments and management facility.
- The software should have a unique option to record your voice and compare against the original master voice of the program, built into fit into any screen.
- The software must also show the

CHANGE TO THE CHANGE

# Raigh!

-44-

correct answers to the students after the exercise and the answers must be shown in different colours to easily highlight and understand.

- The software must give a feedback after the answer for the students to better understanding.
- The software should allow both teacher and student to use any audio or video file as content and also to add subtitles to that file.

# PRE BUILT LESSON PLAN/CONTENTS /EXERCISES

- The software program should be a multiple structured base level program covering four aspects of English language training namely, Listening, Speaking, Reading and Writing (LSRW).
- Listening, comprehension and public speaking skills modules.
- Various etiquettes Group discussion, Interview ,PD and other soft skills modules
- Videos of expert and professional
- Interactive exercises and activities to build the concepts.
- Pronunciation practice using Phonetics

\*Functionality & Prebuilt Lesson Plans Evaluation (demo) will be done by subject experts before ordering

